

LA-UR-18-29663

Approved for public release; distribution is unlimited.

Title: DREAM utilizing real-time Van Allen probe data

Author(s): Walker, Andrew Charles
Morley, Steven Karl

Intended for: CSES Seminar

Issued: 2018-10-11

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.



DREAM utilizing real-time Van Allen Probe Data

Andrew Walker and Steve Morley

October 9th, 2018

UNCLASSIFIED


Outline

- Background
 - Radiation Belts
 - Spacecraft Anomalies
- Motivation
- Data Sources
 - GOES
 - Van Allen Probes
 - Beacon data
 - Science data
- Real-time Pipeline
- Results/Comparisons
- Conclusions


UNCLASSIFIED

Background: Radiation Belts

- Many satellites orbit in the Earth's radiation belts which are zones of energetic charged particles trapped by the Earth's magnetic field
- The radiation belts can undergo large fluctuations from their “quiet-time” state due to geomagnetic storms created by solar activity including:
 - Solar Flares
 - Coronal Mass Ejections




The Earth's Van Allen Radiation Belts.



UNCLASSIFIED

Background: Spacecraft Anomalies

- Energetic charged particles in the radiation belts can induce spacecraft anomalies such as:
 - Single event effects
 - Surface/bulk charging/discharging
 - Total dose effects
- Anomalies can:
 - Corrupt spacecraft data
 - Cause short-term system outages
 - Cause system/subsystem failures
 - Completely incapacitate a spacecraft (e.g. loss of mission)



Arc damage to ESA EURECA solar array (credit: ESA)




Arc damage in laboratory tests (credit: NASA)

UNCLASSIFIED

Background: Space Env. Sensors


- Some spacecraft are equipped with sensors to:
 - Monitor charged particles in the radiation belts
 - Help determine the cause and conditions under which spacecraft anomalies occur
- Most spacecraft are not equipped with space weather instruments
 - They must rely on other satellites in other orbital regimes for information on the radiation belt environment




Measurements from the Magnetospheric Plasma Analyzer (MPA) aboard the geosynchronous LANL-02A satellite on Feb 28th, 2003. Spacecraft surface charging is seen in both the electrons (top) and ions (bottom). [credit: Thomsen et al., 2007]

UNCLASSIFIED

Project Motivation



Assimilation
with
DREAM




- **Generate global estimate of radiation belts with DREAM**
 - Global estimate gives more accurate information for satellites without space environment instruments
 - Better diagnose spacecraft anomalies
 - Better predict conditions that may cause anomalies
 - DREAM is also a framework for better understanding the physical processes that control the radiation belts

UNCLASSIFIED

Project Goal

- Currently, DREAM runs on geosynchronous data from GOES
 - Limited range of L-shell
 - Yields poor prediction for L far from ~6.6 (GEO L-shell)
- Goal: Add the Van Allen Probe real-time data (known as beacon or space weather data) for ingestion into DREAM
 - Covers a large range of L-shell from <2 to ~6
 - Should yield better global prediction of the radiation belts




GOES and Van Allen Probes orbital trajectories on March 7th, 2018. Colors denote L-shell bands. [credit: NOAA]

UNCLASSIFIED

DREAM Framework


- Inputs: Radiation Belt Observations
 - GOES 13
 - Van Allen Probes
 - Beacon
 - Science
- Models
 - 1D Radial Diffusion Radiation Belt Model
 - Tsyganenko 1989 (T89c) Magnetic Field Model
- Output
 - Global phase space density estimate
 - Flux along arbitrary satellite orbit



UNCLASSIFIED

Data Sources: GOES 13


- GOES = Geostationary Operational Environmental Satellite
- Orbital longitude = 60° W
- Electron data from 2 sensor types
- Limited pitch angle coverage
- EPEAD
 - Energetic Proton, Electron, and Alpha Detectors
 - High energy integral fluxes
 - (>0.6 MeV, >2 MeV, >4 MeV)
- MAGED
 - Magnetospheric Electron Detector
 - Low energy differential fluxes
 - 30-50 keV, 50-100 keV, 100-200 keV, 200-350 keV, 350-600 keV



UNCLASSIFIED

Data Sources: Van Allen Probes


- Also known as the Radiation Belt Storm Probes (RBSP)
- Two satellites (A and B)
- Highly elliptical orbits (HEO)
- Electron data from 3 instruments
- MagEIS
 - Magnetic Ion Electron Spectrometers
 - Four types: Low, M35, M75, and High
 - Energy range = ~ 20 keV to ~ 5 MeV
- HOPE (Not used in this work)
 - Helium, Oxygen, Proton, and Electron Mass Spectrometer
 - Low energy sensor – 1 eV to ~ 50 keV
- REPT (Not used in this work)
 - Relativistic Electron-Proton Telescope
 - High energy sensor - ~ 1.5 MeV to ~ 20 MeV



UNCLASSIFIED

Data Sources: RBSP A Beacon


- Real-time Van Allen Probe data
- Also known as “Space Weather” data
- Available for MagEIS, REPT, and HOPE
- MagEIS
 - Only Spin-averaged Electron Flux
 - Must be processed with REPAD to generate pitch angle tagged fluxes
 - Limited temporal coverage
 - ~85% coverage for RBSPA
 - ~35% coverage for RBSPB
- HOPE & REPT
 - Format and lack of compute information make real-time data make it difficult to use



UNCLASSIFIED

Data Sources: RBSP B Beacon


- Real-time Van Allen Probe data
- Also known as “Space Weather” data
- Available for MagEIS, REPT, and HOPE
- MagEIS
 - Only Spin-averaged Electron Flux
 - Must be processed with REPAD to generate pitch angle tagged fluxes
 - Limited temporal coverage
 - ~85% coverage for RBSPA
 - ~35% coverage for RBSPB
- HOPE & REPT
 - Format and lack of compute information make real-time data make it difficult to use



UNCLASSIFIED

Data Sources: RBSP A Science


- Definitive Van Allen Probe data
- Considered the “gold standard” of space environment data
- Available for MagEIS, REPT, and HOPE
- Not a real-time data source
 - Preliminary Level 3 flux files are available in ~12 hours
 - Definitive Level 3 flux files are available in ~1 week




UNCLASSIFIED

Data Sources: RBSP B Science

- Definitive Van Allen Probe data
- Considered the “gold standard” of space environment data
- Available for MagEIS, REPT, and HOPE
- Not a real-time data source
 - Preliminary Level 3 flux files are available in ~12 hours
 - Definitive Level 3 flux files are available in ~1 week



RBSP B unidirectional differential electron flux for pitch angle of 45 degrees.





RBSP B phase space density for specific μ and K .

UNCLASSIFIED


Beacon Data Processing

- Van Allen Probe beacon data must be converted from spin-averaged flux to pitch angle tagged flux
 - Conversion utilizes REPAD
 - REPAD = Relativistic Electron Pitch Angle Distribution Model
- REPAD Model
 - Uses Legendre polynomials to fit pitch angle distributions
 - Trained using data from CRRES, Polar, and LANL-97A
 - Legendre polynomial coefficients depend on:
 - L-shell
 - AE index
 - Magnetic local time
 - Electron energy



UNCLASSIFIED


Beacon vs. Science: Energy



- Van Allen Probe beacon data processed with REPAD compares quite well with the science data (example shown for June 1st, 2016)
 - 3 energies: 32 keV, 143 keV and 1.078 MeV
 - Pitch angle = 45 degrees

UNCLASSIFIED


Beacon vs. Science: Pitch Angle



- Van Allen Probe beacon data processed with REPAD compares well with the science data at lower energies (example shown for June 1st, 2016)
 - 3 energies: 32 keV, 143 keV and 1.078 MeV
 - Time: June 1st, 2016 at 06:00:00

UNCLASSIFIED


Real-time DREAM



- GOES 13 and Van Allen Probe beacon data is now ingested into DREAM in real-time
 - Global phase space density is updated every 30 minutes

UNCLASSIFIED

Real-time DREAM




- Cut-in / cut-out times of Van Allen Probe data lead to discontinuities in the assimilated phase space density
 - Diffusion timescale is much shorter than the longest cut-out time period (~24 hour) in the Van Allen probe beacon data

UNCLASSIFIED

Comparisons: Test Case


- Assimilated PSD is compared between:
 - GOES Only
 - GOES + Beacon
 - GOES + Science
- Time Period
 - Start: 2016-06-01
 - End: 2016-06-10
- Moderate Geomagnetic Storm
 - K_p : 1 to 6
 - DST: ~ -40 to $+30$ nT



UNCLASSIFIED

Comparisons: GOES Only


- With only GOES, there is no radial structure other than provided by the model
- Storm onset near June 5th is clearly visible in DREAM PSD
- Reduction in PSD quickly diffuses away from GEO L-shell



UNCLASSIFIED

Comparisons: GOES + Beacon


- Van Allen Probe Beacon adds additional radial structure at the cost of discontinuities in PSD
- Structure of low L-shell (3 to 4) is significantly enhanced
- Structure of L-shell from 4 to 6 is also enhanced but diffusion occurs at a faster rate in this region so discontinuities are more noticeable



UNCLASSIFIED

Comparisons: GOES + Science

- Van Allen Probe Science data provides the best assimilated PSD but is not an option for real-time processing
- Some discontinuities are still visible, but they are significantly diminished compare to the Beacon data



UNCLASSIFIED

Conclusions

- **Van Allen Probe beacon data processed and ingested by DREAM**
 - Spin-averaged flux converted to pitch angle distribution by REPAD
 - ~85% coverage for RBSP A; ~35% coverage for RBSPB
 - Only utilizing data from MagEIS (~20 keV to ~5 MeV)
- **DREAM PSD compared**
 - GOES only: Little radial structure but does capture PSD drop during storm
 - GOES + Beacon: Adds radial structure but leads to discontinuities in PSD
 - GOES + Science: Most representative PSD but not available for real-time
- **DREAM is running in real-time on GOES 13 and Van Allen Probe beacon data. PSD products are available at:**
 - [/n/space_data/dream/DREAM_PSD](#)

UNCLASSIFIED